

Serial No. 10/052,686

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**List of Claims:**

Claims 1-12 (canceled)

Claim 13 (previously presented) A bottom bracket assembly for a bicycle comprising a spindle that is rotatably held in an outer bracket portion with at least two cartridge bearings, each including outer and inner races, where:

- a) the inner races of said cartridge bearings are fit onto said spindle and the outer races of said cartridge bearings are fit into said outer bracket portion;
- b) both said inner races are fixed on said spindle in both axial directions by abutting inner and outer stop elements;
- c) at least one of said outer races is mounted in said outer bracket portion, said outer race having an initial position such that said outer race is free to move in both axial directions from said initial position.

Claim 14 (original) The bottom bracket of claim 13 in which at least one step is provided on the spindle as an inner stop element.

Claim 15 (original) The bottom bracket of claim 13 in which stop rings are provided as outer stop elements.

Claim 16 (original) The bottom bracket of claim 13 in which said outer bracket portion consists of at least one adapter and a cylindrical sleeve, wherein said adapter and/or said sleeve provide shoulders to limit axial movement of said outer bearing races, and where gaps are provided between the axial end surfaces of said outer race and said shoulders that allow the outer races to move axially.

Serial No. 10/052,686

Claim 17 (currently amended) A bottom bracket assembly for a bicycle comprising a spindle rotatably held in an outer bracket portion with at least two cartridge bearings each including outer and inner races, where:

- a) the inner races of said cartridge bearings are fit onto said spindle and the outer races are fit into said outer bracket portion;
- b) both said inner races are fixed in both axial directions by abutting inner and outer stop elements provided on said spindle;
- c) the ends of said spindle comprise adapting portions to receive crank arms such that said crank arms abut against the outer stop elements in an axial direction;
- d) at least one of said outer races is mounted in said outer bracket portion, said outer race having an initial position such that [[it]] said outer race is free to move in both axial directions from said initial position.

Claim 18 (original) The bottom bracket of claim 17 in which at least one step is provided on the spindle as an inner stop element.

Claim 19 (original) The bottom bracket of claim 17 in which stop rings are provided as outer stop elements.

Claim 20 (original) The bottom bracket of claim 17 in which both outer races are free to move in both axial directions.

Claim 21 (canceled)

Claim 22 (currently amended) A bicycle with two crank arms and attached pedals in which:

- a) said crank arms are connected to a spindle arranged rotatably in a bottom bracket;
- b) said bottom bracket comprises an outer bracket portion and at least two cartridge bearings, each including inner and outer races;

Serial No. 10/052,686

c) the inner races of said cartridge bearings are fit onto said spindle and the outer races are fit into said outer bracket portion, the outer races having an initial position such that the outer race is free to move in both axial directions from said initial position;

d) said spindle includes at least one inner stop element which abuts against both of said inner races in one axial direction, and there are outer stop elements provided which abut against both of said inner races in the other axial direction, such that both of said inner races are fixed on said spindle in both axial directions;

e) the ends of the said spindle comprise adapting portions to receive said crank arms such that said crank arms abut against the outer stop elements in an axial direction.

Claim 23 (new) A bottom bracket assembly for a bicycle comprising a spindle that is notably held in an outer bracket portion with at least two cartridge bearings, each including outer and inner races, where:

the inner races of said cartridge bearings are fit onto said spindle and the outer races of said cartridge bearings are fit into said outer bracket portion;

both said inner races are fixed on said spindle in both axial directions by abutting inner and outer stop elements;

at least one of said outer races is mounted in said outer bracket portion such that it is free to move in both axial directions; and

at least one step is provided on the spindle as an inner stop element.